

04/24/01
JC772 U.S. PTO

PATENT
ATTORNEY DOCKET NO.: 049128-5006

JC885 U.S. PTO
09/840082
04/24/01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
BOX PATENT APPLICATION
Washington, D.C. 20231

**TRANSMITTAL FOR A NEWLY EXECUTED ORIGINAL APPLICATION
UNDER 37 C.F.R. §1.53(b)**

This is a request for filing a patent application under 37 C.F.R. §1.53(b) for:

Inventors: Joo Soo LIM and In Byeong KANG

For: LIQUID CRYSTAL DISPLAY DEVICE AND FABRICATING METHOD THEREOF

1. This is a new ☒ **Utility** ☐ **Design** ☐ **Plant** patent application.
2. The papers enclosed to obtain a filing date are as follows:

<u>17</u>	Pages of Specification including
<u>1</u>	Title Page
<u>6</u>	Pages of Claims
<u>1</u>	Page of Abstract
<u>5</u>	Sheets of drawings containing <u>6</u> Figures

☐ The enclosed drawing(s) are photograph(s), and there is also attached a PETITION TO ACCEPT PHOTOGRAPH(S) AS DRAWING(S)
3. Combined Declaration and Power of Attorney

<input checked="" type="checkbox"/>	Enclosed and is executed by all Inventors.
<input type="checkbox"/>	Not Enclosed.

This application is being filed under the provisions of 37 C.F.R. §1.53(f).
Applicant(s) await notification from the Patent and Trademark Office of the time set for filing the Declaration and paying the filing fees.

4. Language

☒ English☐ Non-English

This application is being filed in accordance with 37 C.F.R. §1.52(d) and §608.01 of the MPEP. Applicant(s) await notification from the Patent and Trademark Office of the time set for filing the verified English translation and the processing fee.

5. Assignment

☒ An assignment of the invention to LG. PHILIPS LCD CO., LTD and a PTO Form-1595, Recordation Form Cover Sheet, are enclosed.

☐ An assignment will be filed at a later date.

6. Priority - foreign applications under 35 U.S.C. §119(a)-(d) or §365(b) or PCT international applications under 35 U.S.C. §365(a) designating at least one country other than the U.S.

☒ Priority of the following foreign application is claimed:

Country	Application No.	Filed
Korea	P00-26876	May 19, 2000

Certified copy: ☒ is attached. ☐ will follow.

7. Priority based on provisional application(s) - 35 U.S.C. §119(e)

☐ Priority of the following provisional application(s) is claimed:

Application No.	Filed

A. Relate Back - 35 U.S.C. §119(e)

☐ Amend the specification by inserting before the first line the sentence:
 "This application claims priority of copending provisional application(s)
 No. _____ filed on _____."

8. Small entity status

☐ A statement claiming small entity status under 37 C.F.R. §§1.9 and 1.27 is enclosed.

9. Fee Calculation (37 C.F.R. §1.16)

CLAIMS FOR FEE CALCULATION				
	Number Filed	Number Extra	at Rate of	Basic Fee Utility \$710.00 Design \$320.00
Total Claims (37 C.F.R. §1.16(c))	20 - 20 =	0	\$ 18.00 each=	\$0.00
Independent Claims (37 C.F.R. §1.16(b))	6 - 3 =	3	\$ 80.00 each=	\$240.00
Multiple dependent claim(s), if any (37 C.F.R. §1.16(d))			\$270.00	+
SUB-TOTAL =				\$950.00
Reduction by 1/2 for filing by a small entity				- \$
TOTAL FILING FEE =				\$950.00

10. Fee Payment

☐ Not Enclosed. **NO FEE IS BEING PAID BY CHECK OR DEPOSIT ACCOUNT AT THIS TIME.**

This application is being filed under the provisions of 37 C.F.R. §1.53(f).
 Applicant(s) await notification from the Patent and Trademark Office of the time set for filing the Declaration and paying the filing fees.

☒ Enclosed.

Two checks in the amounts of \$ 950.00 and \$40.00 representing the basic filing fee of \$710.00, \$240.00 additional independent claims fee and an assignment recording fee of \$40.00 are enclosed.

11. ☒ **Except** for issue fees payable under 37 C.F.R. §1.18, the Commissioner is hereby authorized by this paper to charge any additional fees during the entire pendency of this application including fees due under 37 C.F.R. §§1.16 and 1.17 which may be required, including any required extension of time fees, or credit any overpayment to Deposit Account 50-0310. This paragraph is intended to be a **CONSTRUCTIVE PETITION FOR EXTENSION OF TIME** in accordance with 37 C.F.R. §1.136(a)(3).

12. Additional papers enclosed:

- ☒ Assignment Recordation Cover Sheet
☒ Assignment
☐ Form PTO-1449, ___ document included
☐ Declaration of Biological Deposit
☐ Submission of "Sequence Listing", computer readable copy and/or amendment pertaining thereto for biotechnology invention containing nucleotide and/or amino acid sequence.

Please accord this application an application number and filing date.

Respectfully submitted,

MORGAN, LEWIS & BOCKIUS LLP



Robert J. Goodell

Reg. No. 41,040

Dated: April 24, 2001

Customer No. 009629

MORGAN, LEWIS & BOCKIUS LLP

1800 M Street, N.W.

Washington, D.C. 20036

(202) 467-7000

U.S. PATENT APPLICATION

OF

JOO SOO LIM

FOR

**LIQUID CRYSTAL DISPLAY DEVICE AND
FABRICATING METHOD THEREOF**

[0001] This application claims the benefit of Korean Patent Application No. P00-26876 filed May 19, 2000, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] This invention relates to a liquid crystal display, and more particularly to a liquid crystal display device and method of fabricating the same that reduces a reflectivity of an LCD display screen.

Description of the Related Art

[0003] Generally, a liquid crystal display (LCD) of an active matrix driving system uses thin film transistors (TFT's) as switching devices to display images. Since such LCD's can be made smaller than cathode ray tubes, they have been widely used as monitors for personal computers or notebook computers, as well as in office automation equipment, such as copy machines, etc., and in portable equipment, such as a cellular phones and pagers, etc.

[0004] Referring to FIGS. 1 and 2, in the conventional LCD device, a gate line 14 and a data line 13 is formed on a rear substrate 1 crossing each other, and a pixel electrode 10 is formed at the interior thereof. A TFT 12 is formed at an intersection between the gate line 14 and the data line 13.

[0005] The TFT 12 includes a gate electrode 3, a source electrode 6 and a drain electrode 7 to apply a data signal at the data line 13 to the pixel electrode 10 during an application of a scanning pulse to the gate electrode 3. The gate electrode 3 is connected to the gate line 14, while the source electrode 6 is connected to the data line 13. The drain electrode 7 is connected, via a contact hole 9, to the pixel electrode 10, which is deposited with a transparent conductive material such as indium-tin-oxide (ITO). A gate insulating film 4, deposited using an inorganic

insulating material, is formed on the gate electrode 3 and the gate line 14, and an active layer 20 and an ohmic contact layer 5 are deposited thereon. A passivation layer 8 made from either an inorganic insulating material or an organic insulating material is formed on the TFT 12.

[0006] In the conventional LCD device, a storage capacitor 19 is provided on the gate line 14. The storage capacitor 19 accumulates a driving voltage (charge) of the next scanning line during the previous scanning period, to thereby lower the driving voltage. An upper electrode 15 of the storage capacitor 19 is made from a metal or a metal alloy upon formation of the source electrode 6 and the drain electrode 7, as shown in FIG. 3. The gate line 14 that overlaps the upper electrode 15 serves as a lower electrode of the storage capacitor 19. The upper electrode 15 of the storage capacitor 19 is connected, via a contact hole 16 passing through a passivation layer 8, to the pixel electrode 10.

[0007] A black matrix 11 is provided on a front substrate 2, which is opposed to the rear substrate 1, with a liquid crystal therebetween. The black matrix 11 is positioned at a portion other than an effective display area of a pixel to absorb all wavelengths of light incident thereon. Further, on the front substrate 2 there are provided a common electrode, a color filter and an alignment film (not shown) in addition to the black matrix 11.

[0008] Such an LCD device has a problem in that a large amount of reflective light is generated at the display screen due to a structure of the black matrix 11. More specifically, the black matrix 11 does not overlap with a pixel electrode side portion 17 of the drain electrode 7 and a pixel electrode side portion 18 of the upper electrode 15 of the storage capacitor, as shown in FIG. 1, due to its pattern structure. As a result, as shown in FIGS. 2 and 3, when external light is incident on areas O1 and O2 of the black matrix 11, the upper electrode 15 of the storage capacitor and on the drain electrode 7, it is reflected from the upper electrode 15 and the drain electrode 7, which

are made of metal. Such a reflected light is incident on a user's eye, and reduces the contrast, thereby reducing quality of a displayed image. For instance, since an aircraft cockpit is exposed to direct sunlight, various LCD panels installed in the cockpit of the aircraft generate a large amount of reflected light. Therefore, the LCD panel in an aircraft may have a deterioration of picture clarity due to the reflected light, sometimes causing pilot error.

SUMMARY OF THE INVENTION

[0009] Accordingly, it is an object of the present invention to provide a liquid crystal display and a fabricating method thereof that reduce a reflectivity of the display screen.

[0010] In order to achieve these and other objects of the invention, a liquid crystal display device according to one aspect of the invention includes a pixel electrode at a pixel area between a gate line and a data line, a switching device at an intersection between the gate line and the data line, the switching device comprising a light-shielding member overlapping the switching device and extending from an end at the pixel electrode side of a metal thin film provided within the switching device into the pixel area, for blocking light incident on the metal thin film.

[0011] A liquid crystal display device according to another aspect of the present invention includes a pixel electrode at a pixel area between a gate line and a data line, a charging device on the gate line, the charging device including a metal thin film, a light-shielding member overlapping the charging device and extending from an end at the pixel electrode side of a metal thin film into the pixel area, for blocking light incident on the metal thin film.

[0012] A liquid crystal display device according to still another aspect of the present invention includes a pixel electrode at a pixel area between a gate line and a data line, a thin film transistor at an intersection between the gate line and the data line and including a first metal thin film a storage capacitor on the gate line and including a second metal thin film, a black matrix at a

boundary portion between pixel areas, first dummy black matrix connected to the black matrix and extending from an end at the pixel electrode side of the metal thin film into the pixel area, and a second dummy black matrix connected to the black matrix and extending from an end at the pixel electrode side of the second metal thin film into the pixel area.

[0013] A method of fabricating a liquid crystal display device according to still another aspect of the present invention includes the steps of forming a pixel electrode at a pixel area between a gate line and a data line, forming a switching device including a metal thin film at an intersection between the gate line and the data line, and forming a light-shielding member for blocking light incident on the metal thin film to overlap with the switching device, the light-shielding member extending from an end at the pixel electrode side of a metal thin film of the switching device into the pixel area.

[0014] A method of fabricating a liquid crystal display device according to still another aspect of the present invention includes the steps of forming a pixel electrode at a pixel area between a gate line and a data line, forming a charging device including a first metal thin film on the gate line, and forming a light-shielding member for blocking light incident on the metal thin film to overlap the metal thin film, the light-shielding member extending from an end at the pixel electrode side of the first metal thin film into the pixel area.

[0015] A method of fabricating a liquid crystal display device according to still another aspect of the present invention includes the steps of forming a pixel electrode at a pixel area between a gate line and a data line on a rear substrate, forming a thin film transistor including a first metal thin film at an intersection between the gate line and the data line on the rear substrate, forming a storage capacitor including a second metal thin film on the rear substrate and overlapping the gate line, forming a black matrix on a front substrate opposed to the rear

substrate at a boundary portion between pixel areas, forming a first dummy black matrix extending from an end at the pixel electrode side of the first metal thin film into the pixel area on the front substrate, and forming a second dummy black matrix extending from an end at the pixel electrode side of the second metal thin film into the pixel area on the front substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] These and other objects of the invention will be apparent from the following detailed description of the embodiment of the present invention with reference to the accompanying drawings.

[0017] In the drawings:

[0018] FIG. 1 is a plan view showing a structure of one pixel at a rear substrate of a conventional liquid crystal display device;

[0019] FIG. 2 is a section view of a thin film transistor taken along the line A-A' of FIG. 1;

[0020] FIG. 3 is a section view of a thin film transistor taken along the line B-B' of FIG. 1;

[0021] FIG. 4 is a plan view showing a structure of one pixel at a rear substrate of a liquid crystal display device according to an embodiment of the present invention;

[0022] FIG. 5 is a section view of a thin film transistor taken along the line C-C' of FIG. 4; and

[0023] FIG. 6 is a section view of a thin film transistor taken along the line D-D' of FIG. 4.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0024] As shown in FIGs. 4 and 5, an LCD device according to an embodiment of the present invention includes a gate line 34 and a data line 33 formed on a rear substrate 21 crossing each other. A pixel electrode 30 is formed at the interior thereof. A TFT 32 is formed at an intersection between the gate line 34 and the data line 33.

[0025] The TFT 32 includes a gate electrode 23, a source electrode 26 and a drain electrode 27 to apply a data signal at the data line 33 to the pixel electrode 30 during an "on" period of a

scanning pulse to the gate electrode 23. The gate electrode 23 is connected to the gate line 34 while the source electrode 26 is connected to the data line 33. The drain electrode 27 is connected to the pixel electrode 30.

[0026] A process of fabricating such a TFT will be described below. First, a metal thin film is formed by depositing aluminum (Al) or copper (Cu) on the rear substrate 1 using, for example, a sputtering technique. The metal thin film is selectively patterned, to remain only at a desired portion of the rear substrate 21 using photolithography. A wet etching method may be used for the photolithography. The patterned metal thin film is formed into the gate electrode 23 and the gate line 34.

[0027] Subsequently, an insulating material, such as silicon oxide or silicon nitride, is deposited onto the entire substrate by chemical vapor deposition (CVD) to form a gate insulating film 24. The gate insulating film 24 covers the gate electrode 23 and the gate line 14. An active layer 40 and an ohmic contact layer 25 are sequentially deposited onto the gate insulating film 4 by, for example, CVD. The active layer 40 is made of an amorphous silicon or polycrystalline silicon, and is not doped with impurities. The ohmic contact layer 25 is made of amorphous silicon or polycrystalline silicon, and is doped with n-type or p-type impurities at a high concentration. The active layer 40 and the ohmic contact layer 25 are patterned by photolithography, including isotropic etching, to remain only at a portion corresponding to the gate electrode 23. The source electrode 26 and the drain electrode 27 are formed on the ohmic contact layer 25. The source electrode 26 and the drain electrode 27 are formed by depositing a metal such as molybdenum (Mo), titanium (Ti) or tantalum (Ta), etc., or a molybdenum alloy, such as MoW, MoTa or MoNb, etc. on the ohmic contact layer 25 using CVD or sputtering, and then patterning it. Upon patterning of the source electrode 26 and the drain electrode 27, the

ohmic contact layer 25 on the gate electrode 23 is patterned due to an over-etching, to expose the active layer 40.

[0028] On the TFT 32 that has the structure as described above, an inorganic insulating material such as silicon oxide or silicon nitride, or an organic insulating material such as an acrylic compound, BCB (β -staged-divinyl-siloxane-benzocyclobutene) or PFCB (perfluorocyclobutane), is deposited. The insulating material deposited on the TFT 32 in this manner becomes a passivation layer 28. A portion of the passivation layer 28 covering the drain electrode 27 is patterned. A contact hole 29 exposing the drain electrode 27 is defined in the patterned passivation layer 28. Subsequently, a transparent conductive material, such as ITO or IZO (indium-zinc-oxide), is deposited on the passivation layer 28 and the contact hole 29. The transparent conductive film contacts the drain electrode 27 through the contact hole 29. The transparent conductive film is patterned to remain only at a pixel area between the gate line 34 and the data line 33, thereby forming the pixel electrode 30.

[0029] The LCD device further includes a storage capacitor 39 formed on the gate line 14. The storage capacitor 39 accumulates a driving voltage (charge) for the next scanning line during the previous scanning period, to thereby lower the required driving voltage. An upper electrode 35 of the storage capacitor 39 is formed by patterning a metal or a metal alloy to overlap the gate line 34 upon formation of the source electrode 26 and the drain electrode 27, as shown in FIG. 6. The gate line 34 overlaps the upper electrode 35 and serves as a lower electrode of the storage capacitor 39. The upper electrode 35 of the storage capacitor 39 is connected, via a contact hole 36 formed by patterning of the passivation layer 30, to the pixel electrode 30.

[0030] A black matrix 31 is provided on a front substrate 22, which is opposed to the rear substrate 21, with a liquid crystal therebetween. The black matrix 31 is positioned at a portion

other than an effective display area of a pixel, that is, at a boundary portion between pixels where the TFT 32, the data line 33, the gate line 34 and the storage capacitor 39 are positioned, so as to prevent a color signal interference between pixels and to shut off a reflected light inputted from the display screen. To this end, the black matrix 31 includes a first shield 31a overlapping the TFT 32, and a second shield 31b overlapping the storage capacitor 39. The first shield 31a extends, by a desired distance C1, from an end at the pixel electrode side of the drain electrode 27 as shown in FIG. 5, to thereby absorb light incident to the metal thin film of the TFT 32, including the drain electrode 27. The second shield 31b extends, by a desired distance C2, from an end at the pixel electrode side of the upper electrode 35, as shown in FIG. 6 to absorb light incident to the metal thin film of the storage capacitor 39, including the upper electrode 35. The black matrix 31 is formed on the front substrate 22 by coating an organic material, such as polyimide, to which a black pigment is added. Furthermore, on the front substrate 22 there is a common electrode, a color filter and an alignment film (not shown), in addition to the black matrix 31.

[0031] As described above, the black matrix formed at a boundary portion between pixels extends into the drain electrode of the TFT and the upper electrode of the storage capacitor. Accordingly, a deterioration of contrast caused by a reflected light incident on the metal thin film can be minimized. Such an LCD device is suitable, for example, for a display panel for aircraft cockpits exposed to direct sunlight.

[0032] Although the present invention has been explained by the embodiments shown in the drawings described above, it should be understood by the ordinary skilled person in the art that the invention is not limited to the embodiments, but rather that various changes or modifications

thereof are possible without departing from the spirit of the invention. Accordingly, the scope of the invention shall be determined only by the appended claims and their equivalents.

11/11/2010 11:11:11 AM

What is claimed is:

1. A liquid crystal display device comprising:
a pixel electrode at a pixel area between a gate line and a data line;
a switching device at an intersection between the gate line and the data line, the switching device comprising a light-shielding member overlapping the switching device and extending from an end at the pixel electrode side of a metal thin film provided within the switching device into the pixel area, for blocking light incident on the metal thin film.

2. The liquid crystal display device of claim 1, wherein the light-shielding member is at a front substrate opposed to a rear substrate, the rear substrate including the switching device and the pixel electrode.

3. The liquid crystal display device of claim 2, wherein the light-shielding member is a black matrix.

4. The liquid crystal display device of claim 1, wherein the switching device is a thin film transistor at the intersection between the gate line and the data line for driving the pixel electrode; and

wherein the metal thin film of the switching device is a drain electrode connected to the pixel electrode.

5. A liquid crystal display device comprising:

a pixel electrode at a pixel area between a gate line and a data line;

a charging device on the gate line, the charging device comprising:

a metal thin film;

a light-shielding member overlapping the charging device and extending from an end at the pixel electrode side of a metal thin film into the pixel area, for blocking light incident on the metal thin film.

6. The liquid crystal display device of claim 5, wherein the light-shielding member is formed at a front substrate opposed to a rear substrate that includes the charging device and the pixel electrode.

7. The liquid crystal display device of claim 6, wherein the light-shielding member is a black matrix.

8. The liquid crystal display device of claim 5, wherein the charging device is a storage capacitor including:

an upper electrode formed with the gate line; and

a dielectric layer between the upper electrode and the gate line,

wherein the metal thin film serves as the upper electrode.

9. A liquid crystal display device comprising:

- a pixel electrode at a pixel area between a gate line and a data line;
- a thin film transistor at an intersection between the gate line and the data line and including a first metal thin film;
- a storage capacitor on the gate line and including a second metal thin film;
- a black matrix at a boundary portion between pixel areas;
- a first dummy black matrix connected to the black matrix and extending from an end at the pixel electrode side of the metal thin film into the pixel area; and
- a second dummy black matrix connected to the black matrix and extending from an end at the pixel electrode side of the second metal thin film into the pixel area.

10. The liquid crystal display device of claim 9,

- wherein the first metal thin film is a drain electrode connected to the pixel electrode, and
- wherein the second metal thin film is an upper electrode between the gate line and a dielectric layer.

11. A method of fabricating a liquid crystal display device comprising the steps of:
forming a pixel electrode at a pixel area between a gate line and a data line;
forming a switching device including a metal thin film at an intersection between the gate line and the data line; and
forming a light-shielding member for blocking light incident on the metal thin film to overlap with the switching device, the light-shielding member extending from an end at the pixel electrode side of a metal thin film of the switching device into the pixel area.

12. The method of claim 11, wherein the switching device and the pixel electrode are formed on a rear substrate; and

wherein the light-shielding member is formed on a front substrate opposed to the rear substrate, with a liquid crystal layer therebetween.

13. The method of claim 12, wherein the light-shielding member is a black matrix.

14. The method of claim 12, wherein the switching device is a thin film transistor at the intersection between the gate line and the data line for driving the pixel electrode; and

wherein the metal thin film of the switching device is a drain electrode connected to the pixel electrode.

15. A method of fabricating a liquid crystal display device comprising the steps of:
forming a pixel electrode at a pixel area between a gate line and a data line;
forming a charging device including a first metal thin film on the gate line; and
forming a light-shielding member for blocking light incident on the metal thin film to
overlap the metal thin film, the light-shielding member extending from an end at the pixel
electrode side of the first metal thin film into the pixel area.

16. The method of claim 15, wherein the charging device and the pixel electrode are
formed at a rear substrate; and
wherein the light-shielding member is formed at a front substrate opposed to the rear
substrate with a liquid crystal layer therebetween.

17. The method of claim 16, wherein the light-shielding member is a black matrix.

18. The method of claim 15, wherein the first metal thin film is an upper electrode
over the gate line and a dielectric layer.

19. A method of fabricating a liquid crystal display device comprising the steps of:
forming a pixel electrode at a pixel area between a gate line and a data line on a rear substrate;

forming a thin film transistor including a first metal thin film at an intersection between the gate line and the data line on the rear substrate;

forming a storage capacitor including a second metal thin film on the rear substrate and overlapping the gate line;

forming a black matrix on a front substrate opposed to the rear substrate at a boundary portion between pixel areas;

forming a first dummy black matrix extending from an end at the pixel electrode side of the first metal thin film into the pixel area on the front substrate; and

forming a second dummy black matrix extending from an end at the pixel electrode side of the second metal thin film into the pixel area on the front substrate.

20. The method of claim 19, wherein the metal thin film of the thin film transistor is a drain electrode connected to the pixel electrode; and

wherein the second metal thin film is an upper electrode between the gate line and a dielectric layer.

ABSTRACT

A liquid crystal display device includes a pixel electrode at a pixel area between a gate line and a data line, a switching device at an intersection between the gate line and the data line, the switching device comprising a light-shielding member overlapping the switching device and extending from an end at the pixel electrode side of a metal thin film provided within the switching device into the pixel area, for blocking light incident on the metal thin film.

11/11/2011 11:11:11

FIG.1
CONVENTIONAL ART




FIG.2
CONVENTIONAL ART




FIG. 3
CONVENTIONAL ART




FIG. 4




FIG.5





FIG.6



COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

U.S. DEPARTMENT OF COMMERCE

Patent and Trademark Office

ATTORNEY DOCKET NO.: 049128-5006

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

LIQUID CRYSTAL DISPLAY DEVICE AND FABRICATING METHOD THEREOF

the specification of which:

is attached hereto; or

was filed as United States application Serial No. _____ on _____ and was amended on _____ (if applicable); or

was filed as PCT international application Number _____ on _____ and was amended under PCT Article 19
On _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office information which is material to the patentability of claims presented in this application in accordance with Title 37, Code of Federal Regulations Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate or Section 365(a) of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign applications(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

PRIOR FOREIGN APPLICATION(S):

COUNTRY (if PCT, indicate PCT)	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
Korea	P00-26876	19 May 2000	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No

Combined Declaration for Patent Application and Power of Attorney - (Continued)
(includes Reference to PCT International Applications)
ATTORNEY DOCKET NO.: 049128-5006

I hereby claim the benefits under Title 35, United States Code Section 119(e) of any United States provisional application(s) listed below.

U.S. PROVISIONAL APPLICATIONS

U.S. PROVISIONAL APPLICATION NO.

U.S. FILING DATE:

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) or Section 365(c) of any PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to the patentability of claims presented in this application in accordance with Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT:

U.S. APPLICATIONS		STATUS (Check One)		
U.S. APPLICATION NO.	U.S. FILING DATE	PATENTED	PENDING	ABANDONED

POWER OF ATTORNEY: As a named inventor, I hereby appoint the registered practitioners of Morgan, Lewis & Bockius LLP included in the Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number.

Customer Number: 009629

Direct Telephone Calls To:
(name and telephone number)

Robert J. Gaybrick
202-467-7000

Combined Declaration for Patent Application and Power of Attorney - (Continued)
(includes Reference to PCT International Applications)
ATTORNEY DOCKET NO.: 049128-5006

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME OF SOLE
OR FIRST INVENTOR

Joo Soo LIM

RESIDENCE &
CITIZENSHIP

Kyongsangbuk-do, Republic of Korea

COUNTRY OF
CITIZENSHIP
Republic of Korea

POST OFFICE
ADDRESS

#501-105, Kumyong Apartment, Kwangsang-dong, Kumi-shi,
Kyongsangbuk-do, Republic of Korea

FIRST OR SOLE INVENTOR'S SIGNATURE

LIM, Joo Soo

DATE

April 12, 2001

FULL NAME OF
SECOND INVENTOR

In Byeong KANG

RESIDENCE &
CITIZENSHIP

Kyongsangbuk-do, Republic of Korea

COUNTRY OF
CITIZENSHIP
Republic of Korea

POST OFFICE
ADDRESS

#105-102, Chunggu Apartment, Namtong-dong, Kumi-shi, Kyongsangbuk-do,
Republic of Korea

SECOND INVENTOR'S SIGNATURE

[Signature]

DATE

April 12, 2001

Listing of Inventors Continued on attached page(s): [] Yes [x] No